

Zip HydroTap[®]

Boiling and Chilled filtered water, instantly.
Residential model **Compact Two** – saving time, money and energy at work



The most popular model for home kitchens.



Simple to install at any kitchen sink.



New Free-Flow[™] feature is great for filling a number of personal water bottles at one time as cold filtered water continues to flow even when rated chilled water capacity is exceeded.



Can be installed away from any sink with the optional Zip "font" accessory.

Zip HydroTap offers you boiling and chilled filtered water – instantly.

Simple to operate, and with more safety features than ever.

- Press the red lever and "safety" button together to access boiling water.
- Press the blue lever to fill a glass, jug or bottle with chilled filtered water.
- Lift either lever to run water for any pre-set period of 5 to 15 seconds.
- Boiling water can be isolated during periods your kitchen is unattended.

Smarter technology cuts power consumption dramatically.

- Power-Pulse[™] controls power phasing precisely to cut power costs.
- Set sleep mode to lower boiling water to 64°C after 2 hours of non-use.
- Set hibernation mode to turn off power totally after 2 hours of non-use.
- Set 24/7 on/off weekly timer to save energy when kitchen is not in use.
- Complies with requirements of Section J6 of Building Code of Australia.

Supplied with 0.2 micron water filtration for crystal-clear great-tasting water.

- Filters out chlorine, lead, rust, asbestos fibres and volatile organic compounds.
- Removes impurities larger than one five-thousandth of a millimetre, including the protozoan cysts Cryptosporidium and Giardia. Does not remove fluoride.
- Tested and certified by NSF International to NSF/ANSI standards 42 and 53.

Zip HydroTap®

Boiling and Chilled filtered water, instantly.

Residential model Compact Two – saving time, money and energy at work

Order Code	Zip Model	Boiling Water	Chilled Water	Boiling Chamber	Chilled Chamber	Total Rating	Under-Sink W x D x H
HT1002	Compact 2	Yes	Yes	2.0 Litr	1.5 Litres	1.8 kW	385 x 382 x 348

Location

The tap must be positioned so that it drains into a suitable sink, or be installed on the optional “tap font kit”. The tap should be situated as closely as possible to directly above the under-sink control cabinet. The maximum distance from the base of the tap to the control cabinet is one metre. The under-sink control cabinet must have top, side and rear clearances as shown on the drawings.

Plumbing

To be installed in accordance with AS/NZS3500 plumbing regulations. Designed for direct connection to a potable (drinkable) cold water supply with minimum pressure of 172 kPa and is supplied with a pressure limiting valve that must be connected at the time of installation. An isolating valve should be fixed between the water supply and the operational unit.

Electrical

To be connected to a 10 amp GPO, 220-240 Volt AC power supply and in accordance with AS/NZS 3350 and 3000 wiring regulations.

Caution

In some hard water areas where mineral scale accumulation can become a problem, consideration should be given to the maintenance required. A suitable form of water treatment may be necessary.

Accessories

- 90046 - Tap font kit
- 91290 - Zip 0.2 micron replacement filter
- 91287 - Zip Aire Ventilation system

Warranty

Thirty six months full parts and labour warranty upon registration of the installation with the Zip Customer Care team. For full warranty details visit www.zipindustries.com

Technical Assistance

Contact Zip Industries (Aust) Pty Ltd
67 Allingham Street,
Condell Park NSW 2200.
Free Call 1800 638 633
Telephone 02 9796 3100
Website www.zipindustries.com

As Zip policy is one of continuous product improvement changes to specifications may be made without prior notice.

