Lennox window units



Affordable climate control you'll feel comfortable with

The Lennox window unit (heat pump) air conditioner makes a noticeable difference to your living comfort and wallet. A convenient and cost competitive alternative to high wall splits and heat pumps, the Lennox window unit (heat pump) air conditioner is fast and easy to install in window and wall areas.

Your bedroom, lounge room, study or home office will feel cool in summer and cosy in winter, without heating up your energy bills.





The Lennox window unit (heat pump) air conditioner is also ideal for small commercial venues like retail shops, small offices, on-site work sheds and school office buildings, where ducted air conditioning or split systems are not practical. It's easy on the eye and budget, and provides year-round climate control at the touch of a button.



Lennox window units

Easy on the eye and budget

Features

- MEPS Compliant
- IR Remote Control
- Auto Restart Function after power failure (Suit computer or Equipment room)
- Digital Set point display and Digital room temperature Display
- Separate Cool, Heat, Dehumidify and Auto change over modes
- Three speed Fan
- Vertical Swing Louvers
- Off / On Timer / Sleep Mode
- Fully functional from remote control and from controls on front panel
- Fresh air or recirculate vent function

Window Units - Specifications					
Model Number		LNWR20X		LNWR35X	
PERFORMANCE		COOLING	HEATING	COOLING	HEATING
Capacity	kW	2.23	1.97	3.5	3.2
Input Power	kW	0.66	0.58	1.05	0.96
AEER/COP*	W/W	3.374	3.391	3.33	3.33
Star Rating*		2.0	2.0	2.0	2.0
Indoor Air Flow	L/S	105 / 95 / 86		197 / 180 / 158	
Sound Level db(A)	(Hi/Med/Lo)	51 / 48 / 45		54 / 51 / 48	
Operating Range	°C	17-30		17-30	
ELECTRICAL					
Voltage / Hertz / Phase	V / Ф / Нz	240 / 1 / 50		240 / 1 / 50	
Max Current	А	3.8		6.8	
Starting Current	А	15		25.1	
INSTALLATION					
Unit Dimensions W x H x D	mm	600 x 380 x 560		660 x 428 x 680	
Weight Nett/Gross	kg	34 / 38		47 / 51	
Refrigerant	R410A (g)	530		870	
Moisture Removal	L/h	0.8		1.2	
Application area**	m²	11-18 18-30		-30	

* When tested in accordance with AS/NZS 3823.2

** Subject to heat load calculations

13 23 50

© Copyright 2011 Heatcraft Australia Pty Ltd. Heatcraft Australia continually strive to improve products & processes. We reserve the right to modify product features without notice. Information is correct at the time of printing. LENWU1111

0800 653 330

Available exclusively through Heatcraft Australia and New Zealand **AUSTRALIA NEW ZEALAND**

lennoxaus.com.au





