omega

00887XN

7XN omega 60cm double electric oven



finish	black glass and satin stainless steel
size	888mmH x 594mmW x 561mmD
cutout	880mmH x 560mmW x 550mmD min
capacity	91 litre net (total) top oven: 33 litre bottom oven: 58 litre
installation	flush fitment, underbench or wallmount
door	double glazing
cooking levels	four shelf heights
multifunction	top oven: 4 functions bottom oven: 14 functions
clock	digital
programmability	fully automatic, electronic timer, end-cooking timer, fully programmable clock
lighting	1 x 25W incandescent globe each oven
furniture	baking tray, grill insert, 2 x chrome shelves, wide-grip safety handle for grill tray
warranty	two years parts and labour

MULTIFUNCTION



MULTIFUNCTION

fan forced	for full capacity, swift and even cooking, suitable for most foods	
fan grill	full capacity or small quantities of meat, poultry, fish, infrared radiant heat from above assisted by the rear fan circulating hot, moist air around the food.	
static grill	using only the grill element, the heat is one-directional and is perfect for top browning and very even toasting	
baker's function	concealed floor element and fan only — perforct for dishes with pasty base and filling. the base heat will finish off the pastry without overcooking the filling	
convection	gentler cooking for certain food types using only the perimeter roof element and the concealed floor element	
fan assisted	the rear wall fan, in conjunction with the outer roof element and the concealedfloor element — this function suits most foods and in small quantities	
half static grill	using only the roof element, the heat is one-directional and is perfect for browning and toasting	
bottom element	the base heat element is used for crip pastry, or any dish needing a higher base temperature	
roast PLUS	perfect for cooking and browning both top and bottom of very thick cuts of steak, chicken etc	
top element	to complete cooking of foods — to give a golden brown finish, without cooking from below	
defrost	faster thawing is attained in the safe environment of the oven cavity with the continuous circulation of air at a near-ambient temperature	
boost	For quick preheat, this special function can be activated after selecting a cooking function and is used to reduce the time required to reach the set cooking temperature.	
clean	The oven interior is treated with a micro-porous enamel which transforms food residue into powder for easy cleaning. The turbo clean function is only activated when no cooking function has been selected.	

SUPER STRENGTH ENAMELING

During construction, the oven cavity is baked at 850°C to create a super-strong molecular bonding of the enamel. This ultra-smooth surface is resilient to oxidisation (rusting), pitting and the deleterious effects of cleaning agents and acidic food.

REMOVABLE DOOR

Easily removed, this robust door allows wipe-over maintenance away from the oven. When removed, more ergonomic access to the oven cavity is possible for easier cleaning.

DOUBLE SEAL

Above the oven cavity opening is a double seal. The lower seal prevents the hot, moist and particle-laden cooking air from escaping through the top vents. Only cleaner and cooler air is sent through the deliberate cavity between the inner and outer thermo-reflective glass door panes.

COOLING FAN

An independent cooling fan draws fresh air from the kitchen through apertures below the oven door, then through a cavity between the inner and outer carcase, and finally expels back into the kitchen below the control panel. This circulating fresh air is mixed with warmer vented air from the oven. Cooling air is also forced upward between the glass panes of the door. The air circulation is designed to ensure all external surfaces are safe to touch, the application of the door. The air circulation is eliminated.

Australia's largest online appliance retailer

ID220610 code OO887XN

omega

00887XN

omega 60cm double electric oven



594





WARNING: technical specifications and product sizes can be varied by the manufacturer without notice. Cutouts for appliances should only be by physical product measurements. The above information is indicative only.

ID220610 code OO887XN